



RLD10

Refrigerant Leak Detector

PINPOINTING LEAKS AS EASY AS ONE, TWO!

- Auto zeros when turned on
- LED panel indicates refrigerant leak concentration
- Two position sensitivity selector
- Audible tick rate
- Automatically detects all existing refrigerants and blends



RLD10 • Refrigerant Leak Detector

The RLD10 makes pinpointing leaks as easy as one, two! Detect leaking refrigerant using the high sensitivity mode then switch to the low sensitivity mode to pinpoint its source. If background noise makes the audible tic hard to hear, you can count on the color scaled LED indicators.

The RLD10 has the following features:

- Auto zeros when turned on
- Color scaled LED's indicate refrigerant leak rate
- Two position sensitivity selector
- Audible tick rate
- Long gooseneck probe
- One-hand operation
- Automatically detects all existing halogen refrigerants and blends
- One year limited warranty

Replacement Parts:

Sensor TipRLDTG
 SensorRLDSENS

Optional Accessories:

Soft Carrying CaseAC315
 Hard Carrying CaseAC506

Specifications

Power supply	One 9 volt battery
Sensor	Advanced ionization detection
Sensitivity	.5 oz. per year R134A
Indicators	Audible: Variable tick Visual: Scaled LED array
Warm-up	<10 seconds
Response time	<1 second
Duty cycle	Continuous
Battery life	Approximately eight (8) hours
Probe length	18 - 1/2"
Ambient operating conditions	32° to 102°F (0° to 40°C), 0 to 80% RH (noncondensing)



Distributed By:



1-800-547-5740 • Fax: (503) 643-6322
 www.ueiautomotive.com
 Email: info@ueitest.com

IN CANADA

Vancouver: Phone: 1-877-475-0648 • (604) 278-4511 • Fax: (604) 278-8299
 Toronto: Phone: 1-877-475-0648 • Fax: (905) 238-5117

IN EUROPE

Phone: +44 1707 375550 • Fax: +44 1707 393277

