



# AIR1200

## Infrared Thermometer

### **NON-CONTACT TEMPERATURE TESTING IN THE PALM OF YOUR HAND**

- 12 to 1 Distance To Spot Ratio
- -58° to 1200°F Temperature Range
- UV Leak Detecting Worklight
- Laser Targeting
- MAX Value Capture
- Fixed Emissivity (0.95)
- Backlit Display



Temperature Measurement

**INFRARED**

Featuring The New

**UV WORKLIGHT**

# AIR1200 • IR Thermometer

The AIR1200 is designed to cover the wide range of temperature measurement needs in today's automotive service environment.


Scan radiators for blockage, exhaust manifolds for cylinder variations, pre/post catalytic converters, as well as AC register outlet vents. Check temperature at any other point you can think of from a distance.

Included is a UV worklight that fluoresces most common leak detection dyes, extending the capability of this useful instrument.



## Specifications

Measurement	Non-Contact
<b>AIR1200</b>	
Temperature	-58° to 1200°F (-50° to +649°C)
Accuracy	±1.8°F (1.0°C)  (Target temp = 59°-95°F) (Ambient temp = 77°F)
Accuracy	±2% of reading or 4°F (2°C)  (Target temp = -28°-58°F/96°-932°F) (Ambient temp = 73±3°F)
Distance to Spot	12 : 1
<b>Common</b>	
Resolution (-9.9~199.9°F)	0.1°F (0.1°C)
Response Time (90%)	1 second
Operating Range	32° to 122°F (0° to +50°C)
Emissivity	0.95 fixed
Battery	2 "AAA" Alkaline
Battery Life	Typ. 18 hr/14 hrs continuous use
Dimensions	3.25" (w) x 7" (H) x 1.75" (D)
Weight	7 oz.
Auto Shut Off	15 second idle



Distributed By:



1-800-547-5740 • Fax: (503) 643-6322  
www.ueiautomotive.com  
Email: info@ueitest.com

### IN CANADA

Vancouver: Phone: 1-877-475-0648 • (604) 278-4511 • Fax: (604) 278-8299  
Toronto: Phone: 1-877-475-0648 • Fax: (905) 238-5117

### IN EUROPE

Phone: +44 1707 375550 • Fax: +44 1707 393277

